


emballator

Packaging solutions for future generations

Product specification 881 T/919

Utfärdad av Carl Johan Bonde	Godkänd av Carl Johan Bonde	Verifierad av Leila Moshayyadi	Datum 2023-12-19	Dokument nr. PS-881-32-2	Utgåva 3
------------------------------------	--------------------------------	-----------------------------------	---------------------	-----------------------------	-------------

Product:	32-881 T/919	
Article number:	Please contact our sales department.	
Product Description:	32mm child resistant closure with insert adapted for P32- thread.	
Technical specifications		
Drawings:	Product drawing: S 32-881BST_P26,6strö_00-919 Neck drawing: H 881T	
Sealing:	Insert P26,6 strö	
Plastic resin:	Cover: PPH Closure: PPH Insert: LDPE	
Master batch:	Please contact our sales department.	
Recommended capping torque:	1,5-2,0 Nm	
Recommended storage conditions and time for the packaging material	1 year, keep room temperatured in tightly sealed cardboard boxes.	
Certificate	ZERT – 06941530614-8317 The package can only be designated as child resistant and suitable for adults if certified package are used according to ISO 8317.	
Quality Control		
Standards and norms	Sampling procedure: SS 020130-ISO2859 normal 1 Defect classes according to KP-002	
Delivery		
Packaging	2.000 pcs packed in plastic bag, packed in cardboard boxes 82dm ³ . Labels on the boxes. 16 boxes on each pallet with stretch film wrapped around.	
Traceability	Marking for traceability contains EVP article number, customer article number, production order number, pieces per carton, EVP order number customer order number and date and signature.	